(19) World Intellectual Property Organization International Bureau



- 1801 | 1804 | 1805 | 1805 | 1805 | 1805 | 1805 | 1805 | 1805 | 1805 | 1805 | 1805 | 1805 | 1805 | 1805 | 1805

(43) International Publication Date 28 February 2002 (28.02.2002)

PCT

(10) International Publication Number WO 02/017030 A3

- (51) International Patent Classification7: G05B 19/418
- (21) International Application Number: PCT/US01/26315
- (22) International Filing Date: 22 August 2001 (22.08.2001)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

09/643,614

22 August 2000 (22.08.2000) US

- (71) Applicant (for all designated States except US): ON-WAFER TECHNOLOGIES, INC. [US/US]; 3478 Buskirk Avenue, Suite 1010, Pleasant Hill, CA 94523 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): FREED, Mason, L. [US/US]; 2708 Jones Road, #2, Walnut Creek, CA 94596 (US). MUNDT, Randall, S. [US/US]; 4820 Wingate Drive, Pleasanton, CA 94566 (US). SPANOS, Costas, J. [US/US]; 3292 Springhill Road, Lafayette, CA 94549 (US).
- (74) Agent: WILLIAMS, Larry; 122 Calistoga Road, PMB-301, Santa Rosa, CA 95409-3702 (US).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

- with international search report
- with amended claims
- (88) Date of publication of the international search report: 9 January 2003

Date of publication of the amended claims: 27 March 2003


For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHODS AND APPARATUS FOR OBTAINING DATA FOR PROCESS OPERATION, OPTIMIZATION, MONITORING, AND CONTROL



EXTERNAL COMMUNICATOR

(57) Abstract: Data are collected for deriving response models and information required for developing and maintaining processes and process tools. Methods and apparatus for collecting the data include a sensor apparatus (100) capable of collecting data with less perturbation and fewer disruptions than is usually possible using standard methods. The sensor apparatus is capable of being loaded into a process tool. From within the process tool, one embodiment of the sensor apparatus is capable of measuring data, processing data, storing data, and transmitting data. The sensor apparatus has capabilities for near real time data collection and communication.



12/017030 A3

AMENDED CLAIMS

[received by the International Bureau on 07 January 2003 (07.01.03); original claims 1-3, 5, 11, 13, 14, 16, 17, 19, 21, 23, 24, 27, 32 and 33 amended; new claims 36-38 added; remaining claims unchanged (8 pages)]

- 1. A method of deriving operating characteristics for a process tool used for processing workpieces, the method being performed using a sensor apparatus that includes an information processor and embedded executable commands for controlling the apparatus, the method comprising the steps of:
 - a) loading the sensor apparatus into the process tool;
 - b) measuring the operating characteristics with the sensor apparatus;
 - c) converting the measured operating characteristics into digital data using the sensor apparatus;
 - d) performing at least one step of:
 - i. storing the digital data in the sensor apparatus, and
- ii. storing the digital data in the sensor apparatus and transmitting the digital data to a receiver.
- 2. The method of claim 1 further comprising the steps of: transmitting data wirelessly to the sensor apparatus; and permitting the sensor apparatus to use or store the information wirelessly transmitted to the sensor apparatus.
- 3. A method of deriving operating characteristics for a process tool used for processing workpieces, the method comprising the steps of:
 - a) loading a sensor apparatus including electronic devices into the process tool;
 - b) measuring the operating characteristics with the sensor apparatus;
 - c) converting the measured operating characteristics into digital data using the sensor apparatus;
 - d) performing at least one step of:
 - i. storing the digital data in the sensor apparatus,
 - ii. transmitting the digital data to a receiver, and
 - iii. storing the digital data in the sensor apparatus and transmitting the digital data to a receiver, and
 - e) storing calibration data in the sensor apparatus for use in processing data from the sensors.

- 4. The method of claim 1 further comprising the step of using the sensor apparatus to mathematically manipulate the measured operating characteristics.
- 5. A method of deriving operating characteristics for a process tool used for processing workpieces, the method comprising the steps of:
 - a) loading a sensor apparatus including electronic devices into the process tool;
 - b) measuring the operating characteristics with the sensor apparatus;
 - c) converting the measured operating characteristics into digital data using the sensor apparatus;
 - d) performing at least one step of:
 - i. storing the digital data in the sensor apparatus,
 - ii. transmitting the digital data to a receiver, and
- iii. storing the digital data in the sensor apparatus and transmitting the digital data to a receiver, and
- e) providing sufficient isolation of the sensor apparatus electronic devices to allow the electronic devices to operate in the presence of at least one of electric field, magnetic field, electromagnetic radiation, RF radiation, microwave radiation, temperatures greater than about 100 C, corrosive chemicals, and conditions detrimental to the functioning of the electronic components.
- 6. The method of claim 1 wherein the sensor apparatus comprises a power source and wherein the method of claim 1 further comprises the steps of:

switching the sensor apparatus electronic devices to reduced operation to conserve power while waiting; and

switching the sensor apparatus electronic devices to normal mode after at least one of

- a) a predetermined time,
- b) a predetermined amount of time, and
- c) receiving a command.
- 7. The method of claim 1 wherein the sensor apparatus comprises a power source; and further comprising the step of wirelessly recharging the power source.

WO 02/017030 31

- 8. The method of claim 1 wherein step a) comprises using a robot to load the sensor " apparatus into the process tool.
 - 9. The method of claim 8 further comprising the step of unloading the sensor apparatus from the process tool using the robot.
 - 10. The method of claim 1 wherein the sensor apparatus is approximately the same size as the workpiece so that the sensor apparatus can be loaded into the process tool using a robot used for loading the workpiece.
 - 11. An apparatus for acquiring data for process tools used for processing workpieces, the apparatus comprising:

a substrate;

at least one sensor supported by the substrate, the sensor being capable of providing information;

an information processor supported by the substrate, the information processor having embedded software for controlling the apparatus, the information processor being connected with the sensor so as to receive information from the sensor;

an internal communicator supported by the substrate, the internal communicator being connected with the information processor so that the information processor can provide information to the internal communicator, the internal communicator being capable of transmitting information received from the information processor;

a power source supported by the substrate, the power source being connected so as to provide power to at least one of:

- ì. the information processor,
- ii. the internal communicator, and
- iii. the sensor;

the information processor being capable of at least one of

- a) storing digital information, and
- b) storing digital information and transmitting digital information to the internal communicator.

- 12. The apparatus of claim 11 wherein the at least one sensor comprises a plurality of substantially the same type of sensors or a plurality of sensors that include different types of sensors.
- 13. The apparatus of claim 11 wherein the internal communicator is capable of wirelessly transmitting information to a receiver.
- 14. The apparatus of claim 13 wherein the connection between the information processor and the internal communicator allows bi-directional information transfer and wherein the internal communicator is capable of wirelessly receiving data.
- 15. The apparatus of claim 11 wherein the information processor comprises a microprocessor and a memory, the microprocessor and the memory are connected to allow information transfer.
- 16. The apparatus of claim 15 wherein the memory comprises random access nonvolatile memory.
- 17. The apparatus of claim 11 wherein the power source is capable of being recharged wirelessly and the power source comprises a battery or a capacitor.
- 18. The apparatus of claim 11 wherein the power source comprises a battery and an output voltage regulator, the regulator being connected to the output of the battery so as to provide a substantially constant voltage output for the power source.
- 19. An apparatus for acquiring data for process tools used for processing workpieces, the apparatus comprising:
 - a substrate;
- at least one sensor supported by the substrate, the sensor being capable of providing information;
- an information processor supported by the substrate, the information processor being connected with the sensor so as to receive information from the sensor;
- an internal communicator supported by the substrate, the internal communicator being connected with the information processor so that the information processor can provide

WO 02/017030

information to the internal communicator, the internal communicator being capable of transmitting information received from the information processor;

a power source supported by the substrate, the power source being connected so as to provide power to at least one of:

- i. the information processor,
- ii. the internal communicator, and
- iii. the sensor:

the information processor being capable of at least one of storing digital information, and storing digital information and transmitting digital information to the internal communicator; and wherein the power source is capable of being recharged wirelessly via magnetic induction.

- 20. The apparatus of claim 11 wherein the substrate has a cavity for partially or substantially completely containing at least one of:
 - i. the information processor,
 - ii. the power source, and
 - iii. the internal communicator.
- 21. The apparatus of claim 11 wherein the internal communicator is capable of transmitting information to the exterior of the process tool using sound.
- 22. The apparatus of claim 14 wherein the internal communicator is capable of transmitting and receiving information using energy from the electromagnetic spectrum.
- 23. The apparatus of claim 14 wherein the energy is infrared electromagnetic energy.
- 24. An apparatus for acquiring data for process tools used for processing workpieces, the apparatus comprising:

a substrate;

at least one sensor supported by the substrate, the sensor being capable of providing information;

an information processor supported by the substrate, the information processor being connected with the sensor so as to receive information from the sensor;

an internal communicator supported by the substrate, the internal communicator being - connected with the information processor so that the information processor can provide information to the internal communicator, the internal communicator being capable of transmitting information received from the information processor;

a power source supported by the substrate, the power source being connected so as to provide power to at least one of:

- the information processor,
- ii. the internal communicator, and
- iii. the sensor;

the information processor being capable of at least one of storing digital information, and storing digital information and transmitting digital information to the internal communicator; and

a shield partially or substantially completely surrounding at least one of the information processor, the power source, and the internal communicator; the shield being capable of at least one of:

- allowing the electronic devices to operate under conditions detrimental to the functioning of the electronic devices, and
- substantially preventing exposure of the process tool to contaminants from sensor ii. apparatus.
- 25. The apparatus of claim 20 wherein the substrate is capable of substantially maintaining a vacuum within the cavity.
- 26. The apparatus of claim 20 further comprising a shield, the shield being capable of substantially isolating at least one of
 - į. the information processor,
 - ü. the power source, and
- iii. the internal communicator so that the sensor apparatus can operate when exposed to the process conditions.
- 27. A method of operating a sensor apparatus comprising embedded software for the steps of:
 - a) initializing the sensor apparatus;

WO 02/017030 PCT/US01/26315 35

- b) causing the sensor apparatus to do at least one step of
 - collecting and processing data,
 - ii. sending data to a receiver,
 - iii. storing data, and
 - ív. executing an operational command.
- 28. The method of claim 27 further comprising between step a) and b) the step of causing the sensor apparatus to enter a sleep mode until at least one of
 - i. a predetermined time,
 - ii. a predetermined amount of time, and
 - iii. receiving a command.
- 29. The method of claim 28 wherein the method loops back to the step of entering the sleep mode after completing step b).
- 30. The method of claim 28 further comprising the step of storing calibration data in the sensor apparatus.
- 31. The method of claim 27 further comprising the step of monitoring the level of power of a power source for the sensor apparatus.
- 32. A method of operating a manufacturing facility for processing workpieces, the method comprising the steps of:
 - a) providing at least one process tool capable of processing workpieces, wherein the process tool is part of the manufacturing facility;
 - b) providing a sensor apparatus having embedded software for controlling the sensor apparatus, wherein the sensor apparatus is capable of collecting and wirelessly transmitting or storing data from within the process tool;
 - c) measuring process data for the process tool using the sensor apparatus;
 - d) performing at least one step of
 - i. monitoring the performance of the process tool using data from the sensor apparatus, and
 - maintaining the performance of the process tool in response to the data from the sensor apparatus.

- 33. The method of claim 32 wherein the workpieces comprise substrates for flatpanel displays.
- 34. The apparatus of claim 11 wherein the substrate has dimensions and properties approximately equal to those of the workpiece.
- 35. The apparatus of claim 11 having an area footprint in the range of greater than 0 percent and not greater than about 20 percent of the area of the workpiece.
- 36. The apparatus of claim 11 wherein the power source is capable of being recharged wirelessly via magnetic induction and the power source comprises a battery or a capacitor.
- 37. The method of claim of 1 wherein the information processor comprises a microprocessor.
- 38. The apparatus of claim 11 wherein the information processor comprises a microprocessor.

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 28 February 2002 (28.02.2002)

PCT

(10) International Publication Number WO 02/017030 A3

(51) International Patent Classification⁷: G05B 19/418

- -

(21) International Application Number: PCT/US01/26315

(22) International Filing Date: 22 August 2001 (22.08.2001)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

09/643,614

22 August 2000 (22.08.2000) US

(71) Applicant (for all designated States except US): ON-WAFER TECHNOLOGIES, INC. [US/US]; 3478
Buskirk Avenue, Suite 1010, Pleasant Hill, CA 94523
(US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): FREED, Mason, L. [US/US]; 2708 Jones Road, #2, Walnut Creek, CA 94596 (US). MUNDT, Randall, S. [US/US]; 4820 Wingate Drive, Pleasanton, CA 94566 (US). SPANOS, Costas, J. [US/US]; 3292 Springhill Road, Lafayette, CA 94549 (US).

(74) Agent: WILLIAMS, Larry; 122 Calistoga Road, PMB-301, Santa Rosa, CA 95409-3702 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- (88) Date of publication of the international search report: 9 January 2003

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHODS AND APPARATUS FOR OBTAINING DATA FOR PROCESS OPERATION, OPTIMIZATION, MONITORING, AND CONTROL



(57) Abstract: Data are collected for deriving response models and information required for developing and maintaining processes and process tools. Methods and apparatus for collecting the data include a sensor apparatus (100) capable of collecting data with less perturbation and fewer disruptions than is usually possible using standard methods. The sensor apparatus is capable of being loaded into a process tool. From within the process tool, one embodiment of the sensor apparatus is capable of measuring data, processing data, storing data, and transmitting data. The sensor apparatus has capabilities for near real time data collection and communication.



INTERNATIONAL SEARCH REPORT

rtional Application No PCT/US 01/26315

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 G05B19/418

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols) IPC 7 G05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C DOCUM	ENTS CONSIDERED TO BE HELEVANT		
Category °	Citation of document, with Indication, where appropriate, of the rele	evant passages	Relevant to claim No.
X	US 5 389 769 A (YAMASHITA TEPPEI 14 February 1995 (1995-02-14) the whole document	ET AL)	1,2,5, 7-27, 32-35
X	DE 43 27 342 A (AEG SENSORSYSTEME 23 February 1995 (1995-02-23)	1,2,5, 7-27, 32-35	
Y	the whole document		4,6
Υ	US 5 526 293 A (MOZUMDER PURNENDU AL) 11 June 1996 (1996-06-11) abstract	K ET	4
Y	EP 0 337 669 A (RENISHAW PLC) 18 October 1989 (1989-10-18) abstract 	/	6
χ Furti	ner documents are listed in the continuation of box C.	X Patent family members are listed	in annex.
"A" docume consider in filing de "L" docume which citation "O" docume other i "P" docume later th	ant defining the general state of the art which is not ere:! to be of particular relevance comment but published on or after the international attemption at the international attemption of the state of another content or other special reason (as specified) ent referring to an oral disclosure, use, exhibition or means and published prior to the international filing date but	T' later document published after the inte or priority date and not in conflict with cited to understand the principle or the invention 'X' document of particular relevance; the c cannot be considered novel or cannot involve an inventive step when the do 'Y' document of particular relevance; the c cannot be considered to involve an in document is combined with one or moments, such combined with one or moments, such combination being obvious in the art. '&' document member of the same patent to be passed to the international search.	the application but cory underlying the laimed invention be considered to current is taken atone laimed invention ventive step when the cre other such docurs to a person skilled family
	1 October 2002	07/11/2002	
Name and r	nalling address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL – 2280 HV Rijswijk Tel. (+31–70) 340–2040, Tx. 31 651 epo nl, Fax: (+31–70) 340–3016	Authorized officer Tran-Tien, T	

INTERNATIONAL SEARCH REPORT

ational Application No PCT/US 01/26315

		PCT/US 01/26315			
	ation) DOCUMENTS CONSIDERED TO BE RELEVANT				
Category *	Citation of document, with Indication, where appropriate, of the relevant passages	Relevant to claim No.			
A	WO 00 02236 A (MEMC ELECTRONIC MATERIALS) 13 January 2000 (2000-01-13) abstract	1-35			
A	WO 99 31713 A (JENOPTIK JENA GMBH) 24 June 1999 (1999-06-24) abstract	1-35			
4	US 5 866 024 A (DE VILLENEUVE THIERRY) 2 February 1999 (1999-02-02) abstract	1–35			
A	WO 90 05960 A (CRYPTAG LIMITED ;DEMIC SCIENT LIMITED (GB)) 31 May 1990 (1990-05-31) abstract	1-35			
A	GB 2 141 365 A (GTE VALERON CORP) 19 December 1984 (1984-12-19) abstract	1-35			

INTERNATIONAL SEARCH REPORT

Information on patent family members

ational Application No
PCT/US 01/26315

						
Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 5389769	Α	14-02-1995	JP	3216205	B2	09-10-2001
		2	JР	5275296		22-10-1993
			DE	69325840		09-09-1999
			DE	69325840		25-11-1999
			EP	0562622		29-09-1993
			TW	423709		21-02-2001
DE 4327342	A	23-02-1995	DE ———	4327342	A1	23-02-1995
US 5526293	Α	11-06-1996	US	5661669	A	26-08-1997
EP 0337669	 A	18-10-1989	DE	68916463	D1	04-08-1994
			DE	68916463	T2	17-11-1994
			EP	0337669		18-10-1989
			ĴΡ	2021794		24-01-1990
			ĴΡ	2994401		27-12-1999
			ÜS	5150529		29-09-1992
			EP	0337670		18-10-1989
			JΡ	2015733		19-01-1990
WO 0002236	Α	13-01-2000	TW	452829		01-09-2001
			WO	0002236		13-01-2000
			US	6330971	B1	18-12-2001
WO 9931713	Α	24-06-1999	US	6418352	B1	09-07-2002
			EP	1040511	A2	04-10-2000
			WO	9931713	A2	24-06-1999
			JP	2002509352	T	26-03-2002
			TW	445418	В	11-07-2001
US 5866024	A	02-02-1999	FR	2743194	A1	04-07-1997
			EP	0782001	A1	02-07-1997
			JP	9190519	A	22-07-1997
WO 9005960	Α	31-05-1990	WO	9005960	A1	31-05-1990
GB 2141365	A	19-12-1984	AU	555481	B2	25-09-1986
			AU	2759584		20-12-1984
			BE	899915		01-10-1984
			CA	1237178		24-05-1988
			CH	669842		14-04-1989
			DE	3422181	A1	20-12-1984
			FR	2548349		04-01-1985
			IT	1209553		30-08-1989
			JP	60013202		23-01-1985
			Κ̈́R	9002677		23-04-1990
		•	MX	158057		29-12-1988
			NL	8401874		02-01-1985
			SE	457336		19-12-1988
			SE	8403156		15-12-1984
			US			
				4779319		25-10-1988
			US US	4978857 5065035		18-12-1990
			11	いけいいけん	Δ	12-11-1991
			ZA	8403832		29-01-1986